

MOD. RR2-Z-T-10"

Circular Knitting Machine



Rundstrickmaschinen
Circular Knitting Machines
Machine à tricoter circulaire
Tricofosos circulares
Macchine circolari per maglieria



Wirkmaschinen
Warp Knitting Machines
Machine chaines
Tricofosos por urdimbre
Telai per maglia indemagliabile



Flecht-/Spiralisiermaschinen
Braiders/Spiralizing Machines
Machine à Tresser/Spiralizer
Trenzadoras/Spiralatuçe
Trecciatrici/Espiradora



Sondermaschinen
Special Machines
Machine spécialité
Macchine speciale
Máquina especial



Machine Specifications

Einsatzgebiet:

Rundstrickmaschine zur Herstellung von Fleischverpackungen mit Rippumhängenadel und Platinenabschlag

Maschinenausführung:

- Maschinengröße: 4 - 10" und 2 x 10er - 2 x 16er Teilung lieferbar.
- Antrieb des Strickkopfes erfolgt über einen Zahnriemen und wird stufenlos über einen Frequenzumrichter gesteuert.
- Elektrische Fadenwächter, Gestrickwächter oder Nadelwächter stoppen die Maschine über Frequenzumrichterbremse.
- Separate Aufwickelvorrichtung mit elektrischem Antrieb (bis Durchmesser = 600 mm), stufenlos regelbar mit konstanter Wickelspannung.
- Zum Grundgestrick (feine Teilung) wird ein grobes Maschenmuster mit Rippnadeln erzeugt.

Extra:

- Auswahlssystem über mehr als eine Zylinderumdrehung.
- Größere Aufwickelvorrichtung nach Absprache
- Eine elektromagnetische Bremse gewährleistet ein schnelleres Abbremsen des Maschinenkopfes.
- Fadenzuführung: positive(MPF/MER) oder spannungsbezogene (EFS/SFE - Fabrikat Memminger)
- Verschiedenste Bindungen nach ihren Wünschen.

Teilung und Strickkopfdurchmesser nach Absprache.

Farbe : Hellelfenbein RAL 1015

Konstruktionsänderung vorbehalten!

Application:

Circular knitting machine for meat-packing with dial-needle-transfer and knock over sinkers.

Machine specification:

- Machine Sizes: 4"- 10" and 2 x 10 – 2 x 16 gauge available.
- Drive of knitting head through tooth belt, infinitely controlled through a frequency converter.
- Electrical stop motions, fabric motions or needle detector will stop the machine through frequency converter brake.
- Separate rolling device with electrical drive (maximal Diameter. = 600 mm), infinitely variable with constant rolling tension.
- To the basic knitting (fine gauge) there will be a rough knitting pattern made by dial-needles.

Optional:

- selection over more than 1 cylinder revolution.
- Larger rolling device on request
- An electromagnetic brake ensures fast suppressing of the machine head.
- Yarn feed positive (MPF/MER) or based on tension (EFS/SFE - Manufacturer Memminger)
- Various stitch structures on request.

Gauge and head size on request.

Colour: light ivory RAL 1015

Constructional alteration to change without notice!



MOD. RR2-Z-T-10"

Machine Fabric Samples



Fleischverpackung
Meat-packing

